




Linery TR

Screw terminal blocks

Double deck passthrough

Double deck passthrough



		NSYTRV24D		NSYTRV44D		NSYTRV26T	
Nominal c.s.a.: mm²		2.5		4		2.5	
Type of block		Passthrough - Double deck		Passthrough - Double deck		Passthrough - Triple deck	
Type of connection		2 pole - 1 x 1		2 pole - 1 x 1		3 pole - 1 x 1	
Color		Grey		Grey		Grey	
Max. electric values (Umax, Imax)		500 V, 28 A		800 V, 36 A		500 V, 24 A	
Approximate dimensions: mm (in.)							
Length		69.9 (2.75)		69.9 (2.75)		90 (3.54)	
Height		65 (2.56)		65 (2.56)		77.5 (3.05)	
Width		5.2 (0.21)		6.2 (0.24)		5.2 (0.21)	
Cabling c.s.a.: mm²		2.5		4		2.5	
Flexible cable		0.14 - 4		0.14 - 6		0.14 - 4	
Solid cable		0.14 - 4		0.14 - 6		0.14 - 4	
Nominal electric values							
IEC/EN 60947-7-1		500 V, 24 A		800 V, 30 A		500 V, 20 A	
UL		600 V, 20 A, 26 - 12 AWG		600 V, 30 A, 26 - 10 AWG		600 V, 20 A, 26 - 12 AWG	
CSA		600 V, 20 A, 26 - 12 AWG		600 V, 30 A, 26 - 10 AWG		600 V, 20 A, 26 - 12 AWG	
ATEX ⚡		352 V, 20 A		440 V, 25.5 A		-	
Certifications		UL File E87739 CNN XCFR2, CSA File 256444 Class 6228-01, ATEX, IECEx, GL, LR, DNV, GOST		UL File E87739 CNN XCFR2, CSA File 256444 Class 6228-01, ATEX, IECEx, GL, LR, DNV, GOST		UL File E87739 CNN XCFR2, CSA File 256444 Class 6228-01, GOST	
Terminal blocks							
		Sold in lots of	Catalog number	Sold in lots of	Catalog number	Sold in lots of	Catalog number
Grey		50	NSYTRV24D	50	NSYTRV44D	50	NSYTRV26T
Blue		50	NSYTRV24DBL	50	NSYTRV44DBL	-	-
Accessories							
End stop	Clip-on, 5.2 mm	50	NSYTRAAB35	50	NSYTRAAB35	50	NSYTRAAB35
for 35 mm DIN rail	With screw, 9.5 mm	50	NSYTRAABV35	50	NSYTRAABV35	50	NSYTRAABV35
End plate,	Grey	50	NSYTRACE24	50	NSYTRACE24	50	NSYTRACE26
width 2.2 mm	Grey, partial plate	50	NSYTRACEP24	50	NSYTRACEP24	-	-
Partition plate,	Grey	50	NSYTRAPE24	50	NSYTRAPE24	-	-
width 2 mm	Blue	-	-	-	-	-	-
Plug-in jumper	2-pole	50	NSYTRAL22	50	NSYTRAL42	50	NSYTRAL22
Red	3-pole	50	NSYTRAL23	50	NSYTRAL43	50	NSYTRAL23
	4-pole	50	NSYTRAL24	50	NSYTRAL44	50	NSYTRAL24
	5-pole	50	NSYTRAL25	50	NSYTRAL45	50	NSYTRAL25
	10-pole	10	NSYTRAL210	10	NSYTRAL410	10	NSYTRAL210
	20-pole	10	NSYTRAL220	10	NSYTRAL420	10	NSYTRAL220
Vertical jumper	1-pole	50	NSYTRALV24	50	NSYTRALV24	-	-
Test plug	Metallic part, Ø 2.3 mm	10	NSYTRAATM1	10	NSYTRAATM1	10	NSYTRAATM1
	Insulating sleeve, red	10	NSYTRAATP1	10	NSYTRAATP1	10	NSYTRAATP1
Test adapter	For plug-in jumper shaft	10	NSYTRAFT	10	NSYTRAFT	10	NSYTRAFT
Terminal cover	Yellow	10	NSYTRACS2	10	NSYTRACS4	10	NSYTRACS2
Marker tag holder	For ●AB35 end stop	100	NSYTRASB4	100	NSYTRASB4	100	NSYTRASB4
DIN rail 35 x 7.2 mm	Perforated, 2 m long	20	NSYSDR200BD	20	NSYSDR200BD	20	NSYSDR200BD
Marking accessories		See page 74					
General data							
Strip length: mm (in.)		9 (0.35)		9 (0.35)		9 (0.35)	
Screw thread		M3		M3		M3	
Torque: N•m (lb-in)		0.5 - 0.6 (4.43 - 5.31)		0.6 - 0.8 (5.31 - 7.08)		0.5 - 0.6 (4.43 - 5.31)	