































# Harmony™ XB4 metal 22 mm push buttons

Selector switches with long handle:  
normal and padlockable

Assembly of other products using body/contact assemblies, see page 48; accessories, see page 62


Selector switches with long handle <sup>(1)</sup>									
Screw clamp terminal connections (Schneider Electric anti-retightening system)									
Shape of head	Type of operator	Type of contact		Positions		Reference			
		N/O	N/C	Number	Type				
Complete units									
	Long handle, black	1	–	2-position 90°	Stay put	 <b>ZB4BJ21</b> (ZB4BZ101 + ZB4BJ2)	0.096		
		2	–	3-position ± 45°	Stay put	 <b>ZB4BJ33</b> (ZB4BZ103 + ZB4BJ3)	0.096		
					Spring return to center	 <b>ZB4BJ53</b> (ZB4BZ103 + ZB4BJ5)	0.096		
Heads only									
	Long handle, black			2-position 90°	Stay put	 <b>ZB4BJ2</b>	0.040		
					Spring return from right to left	 <b>ZB4BJ4</b>	0.045		
					3-position ± 45°	Stay put	 <b>ZB4BJ3</b>	0.040	
					Spring return to center	 <b>ZB4BJ5</b>	0.040		
					Spring return from left to center	 <b>ZB4BJ7</b>	0.040		
					Spring return from right to center	 <b>ZB4BJ8</b>	0.040		
			Long handle, padlockable <sup>(2)</sup>			2-position 90°	Stay put	 <b>ZB4BJ291</b>	0.048
								 <b>ZB4BJ292</b>	0.048
						 <b>ZB4BJ294</b>	0.048		
					Spring return from right to left	 <b>ZB4BJ491</b>	0.054		
					3-position ± 45°	Stay put	 <b>ZB4BJ391</b>	0.048	
						 <b>ZB4BJ392</b>	0.048		
						 <b>ZB4BJ393</b>	0.048		
						 <b>ZB4BJ394</b>	0.048		
						 <b>ZB4BJ395</b>	0.048		
						 <b>ZB4BJ396</b>	0.048		
						 <b>ZB4BJ397</b>	0.048		
					Spring return to center	 <b>ZB4BJ593</b>	0.048		
					Spring return from right to center	 <b>ZB4BJ891</b>	0.048		
						 <b>ZB4BJ893</b>	0.048		
						 <b>ZB4BJ895</b>	0.048		
					Spring return from left to center	 <b>ZB4BJ792</b>	0.048		
				 <b>ZB4BJ793</b>	0.048				
				 <b>ZB4BJ796</b>	0.048				

### Heads with black metal bezel

To order, add a figure 7 to the references selected from above.

Example: **ZB4BJ2** becomes **ZB4BJ27**.

<sup>(1)</sup> Recommended maximum number of contacts and sequence of contacts constituting the body (mounting collar + contact) associated with the head, see page 24.

<sup>(2)</sup> The symbol  indicates the padlocking positions.

Note: For contact block and mounting collar ordering information, see pages 48, 50, 51 and 52.