



NMTR2.E221095 Power Circuit and Motor-mounted Apparatus - Component

[Page Bottom](#)

Power Circuit and Motor-mounted Apparatus - Component

[See General Information for Power Circuit and Motor-mounted Apparatus - Component](#)**GINO AG**

E221095

ELEKTROTECHNISCHE FABRIK
FRIEDRICH-WOEHLER-STRASSE 65
53117 BONN, GERMANY

Braking resistors, open type, Model(s) Series 3PR3, followed by 0, 2, 4, 6 or 8, followed by 01, 02, 03, 04 or 05, followed by additional characters.

Series GWG, followed by 1, followed by 4, 5 or 6, followed by 0, 2 or 4, followed by additional characters.

Miscellaneous apparatus, dynamic breaking resistors, Model(s) Series BEG, followed by 6, 10 or 12, followed by NW, followed by 3, 8 or 12, followed by the letter R, may or may not be followed by one digit. Alternative designation 6SE6400-4BC22-5FAO, 6SE6400-4BD24-OFAO, 6SE6400-4BE24-2FAO.

Series BCG or Series BEG, followed by T or blank, followed by 1, 2, 3, 4 or 5, followed by 2, 3, 4, 5 or 7, followed by 0 or 2, followed by the sum of resistive element, followed by the Resistive value in Ohm, followed by additional characters; Alternate Product names VW3A7704, VW3A7705, VW3A7706, VW3A7707, VW3A7708, VW3A7709, ERBG012R05K2, ERBG018R04K3, ERBG015R06K2, ERBG015R03K3, ERBG015R10K0, ERBG023D05K6, ERBG028D04K1, ERBG035D03K3, ERBG043D03K0, ERBG005R02K6, 6SL3000-1BH31-3AA0, 6SL3000-1BH32-5AA0, 6SL3000-1BE31-3AA0, 6SL3000-1BE32-5AA0, 6SL3000-1BF31-3AA0, 6SL3000-1BF32-5AA0, 6SE6400-4BD22-2EA1, 6SE6400-4BD26-OFAO, ERBG012R01K9, ERBG075D01K9, BR30542K1-T-PF, BR30542K7-T-PF, BR30543K4-T-PF.

Series DEG, followed by L, followed by T, followed by 1, 2, 3 or 4, followed by VPR, followed by the Power rating of one resistor element, followed by L or S, followed by "-" followed by the Resistive value in Ohm, followed by additional characters. Alternate product names VW3A7701, VW3A7702, VW3A7703, BR1075250-T-PF, BR1075600-T-PF, BR1075800-T-PF, BR1054400-T-PF, BR1054800-T-PF.

VPR, followed by 80, 100, 120, 150, 200, 300, 400 or 500 followed by L or S, followed by resistor value.

Miscellaneous apparatus, dynamic breaking resistors, open type, Model(s) Series DEG, followed by 1 thru 6, followed by VPR, followed by 80, 120, 150, 200, 300 or 500, followed by X, L or S, followed by 6, 8, 10, 15, 27, 39, 56, 68, 82, 120, 160, 180, 390, followed by the letter R and may or may not be followed by one digit. Alternative designation 6SE6400-4BC05-0AA0, 6SE6400-4BD11-0AA0, 6SE6400-4BC11-2BA0, 6SE6400-4BD12-0BA0, 6SE6400-4BC12-5CA0, 6SE6400-4BC13-0CA0, 6SE6400-4BD16-5CA0, 6SE6400-4BE14-5CA0, 6SE6400-4BE16-5CA0, 6SE6400-4BC18-0DA0, 6SE6400-4BD21-2DA0, 6SE6400-4BE21-3DA0, 6SE6400-4BC21-2EA0, 6SE6400-4BD22-2EA0, 6SE6400-4BE21-8EA0, 6SL3201-0BE12-0AA0, 6SL3201-0BE12-0AA0.

Marking: Company name and model designation.

[Last Updated](#) on 2012-01-24

[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2014 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2014 UL LLC".