



Confirmation of Product Type Approval 13/FEB/2009

Please refer to the "Service Restrictions" shown below to determine if Unit Certification is required for this product.

This is to certify that, pursuant to the Rules of the American Bureau of Shipping (ABS), the manufacturer of the below listed product held a valid Manufacturing Assessment (MA) with expiration date of 03/JUN/2013. The continued validity of the Manufacturing Assessment is dependent on completion of satisfactory audits as required by the ABS Rules.

And; a Product Design Assessment (PDA) valid until 10/NOV/2013 subject to continued compliance with the Rules or standards used in the evaluation of the product.

The above entitle the product to be called Product Type Approved.

The Product Design Assessment is valid for products intended for use on ABS classed vessels, MODUs or facilities which are in existence or under contract for construction on the date of the ABS Rules used to evaluate the Product.

ABS makes no representations regarding Type Approval of the Product for use on vessels, MODUs or facilities built after the date of the ABS Rules used for this evaluation.

Due to wide variety of specifications used in the products ABS has evaluated for Type Approval, it is part of our contract that; whether the standard is an ABS Rule or a non-ABS Rule, the Client has full responsibility for continued compliance with the standard.

SCHNEIDER ELECTRIC - SQUARE D Model Name(s): MCC Model 6 (Square D Brand)

Presented to:

SCHNEIDER ELECTRIC - SQUARE D
1990 SANDIFER BLVD.
SENECA
SC 29678
United States

Intended Service:

Power distribution, control, and protection of motor and non-motor loads for multiple applications on board ABS Classed Vessels, Offshore Rigs and Platforms and Marine applications in other MODUs or Facilities.

Description:

Motor Control Center (MCC) Model 6 provides Group Motor Control for a variety of applications. The MCC Model 6 utilizes an industrial heavy-duty structure and bus design integrating electromechanical Starters, Variable Speed Drives Altivar 61 and Altivar 71, Reduced Voltage Starters Altistart 48, and other solutions as well as non-motor electrical distribution.

Ratings:

2500 Amp maximum horizontal bus 600 Amp maximum vertical bus 600Volt maximum, 1 phase or 3 phase, three or four wire Enclosure: NEMA 1, 1A, 12

Service Restrictions:

1. Motor controllers of 100 kW (135 HP) and over for essential services must be unit certified. 2. Propulsion of vessels other than bow thrusters does not fall under applications covered by MCC Model 6.

Comments:

Motor Control Centers and Controllers enclosure IP/UL/NEMA rating to be based on 4-8-3/Table 2 of the Rules.

Notes / Documentation:

This Product Design Assessment (PDA) is valid only for products intended for use on ABS classed vessels, MODUs or facilities which are in existence or under contract for construction on the date of the ABS Rules used to evaluate the Product.

Term of Validity:

This Design Assessment Certificate number 08-HS391227-PDA, dated 11/Nov/2008 will expire on 10/Nov/2013 or at an earlier date should there be alterations to the product's design or changes to the referenced ABS Rules and other specifications, which affect the product. Product use on or after 1 January 2009, will be subject to compliance with the ABS Rules or specifications in effect when the vessel, MODU or facility is contracted. The product's acceptability on board ABS-classed vessels or facilities is defined in the service restrictions of this certificate.

ABS Rules:

2008 Steel Vessels Rules 1-1-4/7.7, 4-8-3/1.11, 4-8-3/Table 2, 4-8-4/9

National Standards:

UL File: E40610, Volume 11 (UL 845)

International Standards:**Government Authority:****EUMED:****Others:**

ABS Programs

ABS has used due diligence in the preparation of this certificate and it represents the information on the product in the ABS Records as of the date and time the certificate was printed. Type Approval requires Drawing Assessment, Prototype Testing and assessment of the manufacturer's quality assurance and quality control arrangements. Limited circumstances may allow only Prototype Testing to satisfy Type Approval. The approvals of Drawings and Products remain valid as long as the ABS Rule, to which they were assessed, remains valid. ABS cautions manufacturers to review and maintain compliance with all other specifications to which the product may have been assessed. Further, unless it is specifically indicated in the description of the product; Type Approval does not necessarily waive witnessed inspection or survey procedures (where otherwise required) for products to be used in a vessel, MODU or facility intended to be ABS classed or that is presently in class with ABS. Questions regarding the validity of ABS Rules or the need for supplemental testing or inspection of such products should, in all cases, be addressed to ABS.