

TeSys™ K-line Mini-Contactors and Starters

Selection of Auxiliary Contacts and Timers

Instantaneous Auxiliary Contact Blocks for Type LC•K and LP•K Contactors

Recommended for standard applications. Clip-on front mounting, 1 block per contactor

Type of Connection	Type of Contactor	Auxiliary Contacts		Catalog Number	Weight lb. (kg)
		N.O.	N.C.		
Screw Clamp	LC1, LC2 LC7, LC8 LP1, LP2 3- or 4-pole	2	–	LA1KN20	0.10 (0.045)
		–	2	LA1KN02	0.10 (0.045)
		1	1	LA1KN11	0.10 (0.045)
		4	–	LA1KN40	0.10 (0.045)
		3	1	LA1KN31	0.10 (0.045)
		2	2	LA1KN22	0.10 (0.045)
		1	3	LA1KN13	0.10 (0.045)
		–	4	LA1KN04	0.10 (0.045)
Slip-on 1 x 0.25 in. or 2 x 0.11 in.	LC1, LC2 LC7, LC8 LP1, LP2 3- or 4-pole	2	–	LA1KN207	0.10 (0.045)
		–	2	LA1KN027	0.10 (0.045)
		1	1	LA1KN117	0.10 (0.045)
		4	–	LA1KN407	0.10 (0.045)
		3	1	LA1KN317	0.10 (0.045)
		2	2	LA1KN227	0.10 (0.045)
		1	3	LA1KN137	0.10 (0.045)
		–	4	LA1KN047	0.10 (0.045)
Spring Terminals	LC1, LC2 LP1, LP2 3- or 4-pole	2	–	LA1KN203	0.10 (0.045)
		–	2	LA1KN023	0.10 (0.045)
		1	1	LA1KN113	0.10 (0.045)
		4	–	LA1KN403	0.10 (0.045)
		3	1	LA1KN313	0.10 (0.045)
		2	2	LA1KN223	0.10 (0.045)
		1	3	LA1KN133	0.10 (0.045)
		–	4	LA1KN043	0.10 (0.045)

With terminal referencing conforming to standard EN 50012. Clip-on front mounting, 1 block per contactor


Screw clamp with terminal referencing conforming to standard EN 50012 ▲	LC1, LC2 LC7, LC8 LP1, LP2 3-pole + N.O.	–	2	LA1KN02M	0.10 (0.045)
		1	1	LA1KN11M	0.10 (0.045)
		3	1	LA1KN31M	0.10 (0.045)
		2	2	LA1KN22M	0.10 (0.045)
	LC1, LC2 LC7, LC8 LP1, LP2 4-pole	1	3	LA1KN13M	0.10 (0.045)
		1	1	LA1KN11P	0.10 (0.045)
		2	2	LA1KN22P	0.10 (0.045)

▲ See pages 59 and 60 for actual terminal markings.

Electronic Time-Delay Auxiliary Contact Blocks for Type LC•K and LP•K Contactors

- Relay output, with common point changeover contact, AC or DC 240 Vac, 2 A maximum.
- Control voltage: 0.85 to 1.1 Vc.
- Maximum switching capacity: 250 VA or 150 W.
- Operating temperature: -10 to +60 °C (14 to 140 °F).
- Reset time: 1.5 s during the time delay period, 0.5 s after the time delay period.

Clip-on front mounting, 1 block per contactor

Voltage	Type	Timing Range s	Auxiliary Contacts	Catalog Number	Weight lb. (kg)
			SPDT		
V					
AC or DC 24 to 48	On-delay	1 to 30	1	LA2KT2E	0.09 (0.040)
AC 110 to 240	On-delay	1 to 30	1	LA2KT2U	0.09 (0.040)