

Date : July 2, 2020

Subject : **Operating voltage of BMXFTW301/501/1001**

**Dear Schneider Electric Customer,**

BMXFTW301/501/1001 are our preassembled cordsets, one end with 20-way spring-type removable terminal block (BMXFTB2020) while the other end with color-coded flying leads.

Although not indicated in our product documentation, our R&D department has thoroughly checked and confirms that these X80 IO modules related pre-assembled cordsets (commercial references BMXFTW\* both in standard and shielded versions) have technical specifications which allow them to support up to 220V AC current usage. We are planning to update the user documentation with this data in our next release

Schneider Electric is thanking you for your trust in our products and solutions and will continue to do our best to remain your favourite automation provider.

Best Regards,

**Chao CHEN**

Global Offer Manager Modicon M340  
Industrial Automation – Digital Plant LoB

**Schneider Electric**  
**Industrial Automation – Digital Plant LoB**

Postal address :  
8<sup>ème</sup> Rue – 70 Mètres  
F-06510 CARROS

Legal information / Mentions légales  
Société par actions simplifiée au capital de 370.000.000 Euros  
RCS Nanterre : 421 106 709 – Code APE : 3320C  
Siret établissement : 421 106 709 009 40  
N° Identification : TVA FR93 421 106 709  
Siège Social : 35 Rue Joseph Monier – F 92500 Rueil Malmaison