

**Table 61: Motor Protecting Output Filters—480 V Rated Type 1 Enclosed Motor Protection Output Filters (UL 508A)**

Horsepower  Drive 460 V Rating	Amperes	KLCUL Filter Enclosed Part Number	\$ Price	Approximate Weight (lbs)	Enclosure Dimensions					
					H		W		D	
					IN	mm	IN	mm	IN	mm
1–2	4	KLCUL4A1	1126.00	15	12.25	311	12.50	318	6.75	171
3	6	KLCUL6A1	1148.00	15	12.25	311	12.50	318	6.75	171
5	8	KLCUL8A1	1171.00	15	12.25	311	12.50	318	6.75	171
7.5	12	KLCUL12A1	1224.00	15	12.25	311	12.50	318	6.75	171
10	16	KLCUL16A1	1249.00	17	12.25	311	12.50	318	6.75	171
15	25	KLCUL25A1	1355.00	20	12.25	311	12.50	318	6.75	171
20–25	35	KLCUL35A1	1485.00	20	12.25	311	12.50	318	6.75	171
30	45	KLCUL45A1	1535.00	20	12.25	311	12.50	318	6.75	171
40	55	KLCUL55A1	1672.00	20	12.25	311	12.50	318	6.75	171
50–60	80	KLCUL80A2	2178.00	56	19.13	486	15.50	394	15.50	394
75	110	KLCUL110A2	3005.00	60	19.13	486	15.50	394	15.50	394
100	130	KLCUL130A2	3368.00	66	19.13	486	15.50	394	15.50	394
125	160	KLCUL160A2	3617.00	80	19.13	486	15.50	394	15.50	394
150	200	KLCUL200A3	3766.00	102	22.13	562	20.50	521	24.37	619
200	250	KLCUL250A3	3841.00	110	22.13	562	20.50	521	24.37	619
250	300	KLCUL300A3	3863.00	115	22.13	562	20.50	521	24.37	619
300	360	KLCUL360A3	4300.00	125	22.13	562	20.50	521	24.37	619
350	420	KLCUL420A3	4659.00	145	22.13	562	20.50	521	24.37	619
400	480	KLCUL480A3	5221.00	150	22.13	562	20.50	521	24.37	619
450–500	600	KLCUL600A3	5393.00	167	22.13	562	20.50	521	24.37	619

**NOTE:** Line reactors and filters are intended for separate mounting and wiring by the user.

Based on NEC™ (NFPA™ 70) 430–150 current ratings. If drive has higher FLA rating, use the “amperes” rating to select the appropriate filter.