

VW3A4555

line/motor choke - 0.5 mH - 60 A - 3 phases - 94 W -
for variable speed drive



Main

Range of product	Altivar
Product or component type	Line/motor choke
Product compatibility	LXM32MD85N4 - line choke - 1 per drive LXM32MC10N4 - line choke - 1 per drive ATV61CD15N4 - motor choke - 1 per drive ATV61HD11M3X - line choke - 1 per drive ATV61HD15N4 - motor choke - 1 per drive ATV61HD18N4 - line choke - 1 per drive ATV61HD22N4 - line choke - 1 per drive ATV61HD30Y - line choke - 1 per drive ATV61HD37Y - line choke - 1 per drive ATV61HD45Y - line choke - 1 per drive ATV61HU75M3 - line choke - 1 per drive ATV61KD15N4 - motor choke - 1 per drive ATV61WD18N4 - line choke - 1 per drive ATV61WD18N4C - line choke - 1 per drive ATV61WD22N4 - line choke - 1 per drive ATV61WD22N4C - line choke - 1 per drive ATV71HD11M3X - line choke - 1 per drive ATV71HD18N4 - line choke - 1 per drive ATV71HD22N4 - line choke - 1 per drive ATV71HD30Y - line choke - 1 per drive ATV71HD37Y - line choke - 1 per drive ATV71HD45Y - line choke - 1 per drive ATV71HU75M3 - line choke - 1 per drive ATV71WD18N4 - line choke - 1 per drive ATV71WD22N4 - line choke - 1 per drive ATV312HD11M3 - line choke - 1 per drive ATV312HD15M3 - line choke - 1 per drive ATV32HD15N4 - motor choke - 1 per drive Variable speed drive ATV340 motor : 15 kW - 380...480 V - line choke - 1 per drive Variable speed drive ATV340 motor : 18 kW - 380...480 V - line choke - 1 per drive Variable speed drive ATV340 motor : 22 kW - 380...480 V - line choke - 1 per drive Variable speed drive ATV320 motor : 15 kW - 380...500 V - three phase - motor choke - 1 per drive Variable speed drive ATV320 motor : 11 kW - 200...240 V - three phase - line choke - 1 per drive Variable speed drive ATV320 motor : 15 kW - 200...240 V - three phase - line choke - 1 per drive
Network number of phases	Three phase
Range compatibility	Altivar 312 Altivar 61 Altivar 71 Altivar 32 Lexium 32 Lexium 62 Altivar Machine ATV320 Altivar Machine ATV340
Device application	Reduction of current harmonics Reduction of overvoltages at motor terminals
Value of inductance	0.5 mH
[In] rated current	60 A
Thermal losses	94 W
Electrical connection	Terminal 35 mm ² / AWG 0, 2.5...3 N.m

Complementary

Supply frequency	50...60 Hz
Max current	1.65 x nominal current for 60 s

Voltage drop at rated load	3...5 %
Electrical insulation class	Class F
Clearance distance	5.5 mm conforming to IEC 60664
Leakage distance	11.5 mm conforming to IEC 60664
Product weight	11 kg
Width	180 mm
Height	210 mm
Depth	165 mm

Environment

standards	EN 50178 IEC 60076 (with HD398) VDE 0160 level 1
IP degree of protection	IP00 (choke) IP10 (terminals)
environmental characteristic	3B1 conforming to IEC 721-3-3 3C2 conforming to IEC 721-3-3 3S1 conforming to IEC 721-3-3
pollution degree	2 conforming to EN 50178
vibration resistance	1.5 mm peak to peak (f = 3...13 Hz) conforming to IEC 60068-2-6 1 gn (f = 13...200 Hz) conforming to IEC 60068-2-6
shock resistance	15 gn for 11 ms conforming to IEC 60068-2-27
relative humidity	<= 95 %
ambient air temperature for operation	> 45...< 55 °C with current derating of 2 % per °C 0...45 °C without current derating
ambient air temperature for storage	-25...70 °C
operating altitude	<= 1000 m without current derating <= 1000 m without derating


Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0801 - Schneider Electric declaration of conformity

Contractual warranty

Warranty period	18 months
-----------------	-----------

Dimensions




Dimensions in mm

a	b	c1	G	G1	H	Ø
180	210	160	85	122	105	6 x 12

Dimensions in in.


a	b	c1	G	G1	H	Ø
7.09	8.27	6.30	3.35	4.80	4.13	0.24 x 0.47

Recommended Schema - Line Choke



- (1) Line Choke
- (2) Drive

Recommended Schema - Motor Choke



- (1) Motor Choke
- (2) Drive