



Main

Range of product	PowerLogic PM800
Device short name	PM870
Product or component type	Power meter

Complementary

Power quality analysis	Up to the 63rd harmonic
Type of measurement	Energy Power factor (total) Power factor (per phase) Apparent power (total) Apparent power (per phase) Active power (total) Active power (per phase) Reactive power (total) Reactive power (per phase) Voltage Current Frequency
[Us] rated supply voltage	125...250 V DC 115...415 V AC (45...67 Hz) 115...415 V AC (350...450 Hz)
Network frequency	45...67 Hz 350...450 Hz
Power consumption in VA	15 VA
Display type	Backlit LCD
Display resolution	6 lines
Sampling rate	128 samples/cycle
Measurement current	5 A 1 A
Analogue input type	Current 0.005...10 A (impedance $\leq 0.1 \Omega$)
Measurement voltage	0...600 V AC phase to phase 0...347 V AC phase to neutral

Number of inputs	1 digital 0...5 mA 24...125 V AC/DC
Measurement accuracy	± 0.2 % energy ± 0.01 Hz frequency ± 0.002 power factor ± 0.2 % power ± 0.5 % current (0.5...10 A) ± 0.2 % voltage (10...227 V)
Accuracy class	Class 0.5S (active energy according to IEC 62053-22) Class 2 (reactive energy according to IEC 62053-23) Class 0.2 (active energy according to ANSI C12.20)
Number of outputs	1 digital (static)
Communication port protocol	Modbus: 38.4 kbauds,
Communication port support	RS485
Data recording	Alarms Event logs Min/Max of instantaneous values Time stamping Trending/Forecasting GPS synchronisation 4 data logs and PQ sag/swell
Memory capacity	800 kB

Environment

Electromagnetic compatibility	Immunity to impulse waves, conforming to IEC 61000-4-12 Limits for harmonic current emissions, conforming to IEC 61000-3-2 Conducted and radiated emissions, conforming to EN 55011 class A Susceptibility to electromagnetic fields class class III, conforming to IEC 61000-4-3 Conducted RF disturbances class class III, conforming to IEC 61000-4-6 Electrostatic discharge immunity test class class III, conforming to IEC 61000-4-2 Electrical fast transient/burst immunity test class class III, conforming to IEC 61000-4-4 1.2/50 μ s shock waves immunity test class class III, conforming to IEC 61000-4-5 Immunity to impulse waves class class III, conforming to IEC 61000-4-8 Immunity to microbreaks and voltage drops class class III, conforming to IEC 61000-4-11 Limitation of voltage changes, voltage fluctuations and flicker in low-voltage, conforming to IEC 61000-3-3
Mounting mode	Flush-mounted
Mounting support	Panel
Type of installation	Indoor installation
Overvoltage category	III
IP degree of protection	IP30 (back) conforming to IEC 60529 IP52 (front face) conforming to IEC 60529
Relative humidity	90 % 40 °C
Pollution degree	2
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C
Operating altitude	0...3000 m
Standards	IEC 61010-1 UL 508 CSA C22.2 No 14
Product certifications	CE cULus
Width	96 mm
Depth	70 mm
Height	96 mm
Product weight	0.6 kg

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1002 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold

Reference not containing SVHC above the threshold

Product environmental profile

Available

 End of life manual

Product end of life instructions

Available

Contractual warranty

Warranty period

18 months