

GV CIRCUIT BREAKERS - SHORT CIRCUIT CURRENT RATING

UL STANDARD APPLICATIONS

		SCCR - Short Circuit Current Rating - kA						
		System Voltage						
		240 V	480 V		600 V		480Y/277 V	600Y/347 V
Reference	thermal trip setting range	without limiter	without limiter	with GV1L3 limiter	without limiter	with GV1L3 limiter	without limiter	without limiter
GV2ME01	0.1-0.16	50	50	-	30	-	-	-
GV2P01	0.1-0.16	50	50	-	30	-	-	-
GV2ME02	0.16-0.25	50	50	-	30	-	-	-
GV2P02	0.16-0.25	50	50	-	30	-	-	-
GV2ME03 / GV2RT03	0.25-0.40	50	50	-	30	-	-	-
GV2P03	0.25-0.40	50	50	-	30	-	-	-
GV2ME04 / GV2RT04	0.40-0.63	50	50	-	30	-	-	-
GV2P04	0.40-0.63	50	50	-	30	-	-	-
GV2ME05 / GV2RT05	0.63-1.0	50	50	-	30	-	-	-
GV2P05	0.63-1.0	50	50	-	30	-	-	-
GV2ME06 / GV2RT06	1.0-1.6	50	50	-	30	-	-	-
GV2P06	1.0-1.6	50	50	-	30	-	-	-
GV2ME07 / GV2RT07	1.6-2.5	50	50	-	30	-	-	-
GV2P07	1.6-2.5	50	50	-	30	-	-	-
GV2ME08 / GV2RT08	2.5-4.0	50	50	-	30	-	-	-
GV2P08	2.5-4.0	50	50	-	30	-	-	-
GV2ME10 / GV2RT10	4.0-6.3	50	50	-	30	-	-	-
GV2P10	4.0-6.3	50	50	-	30	-	-	-
GV2ME14 / GV2RT14	6-10	30	30	50	30	-	-	-
GV2P14	6-10	50	50	-	30	-	-	-
GV2ME16 / GV2RT16	9-14	25	25	50	10	30	-	-
GV2P16	9-14	50	50	-	18	-	-	-
GV2ME20 / GV2RT20	13-18	25	25	50	10	30	-	-
GV2P20	13-18	50	50	-	18	-	-	-
GV2ME21 / GV2RT21	17-23	25	10	50	10	30	-	-
GV2P21	17-23	50	50	-	18	-	-	-
GV2ME22	20-25	25	10	50	10	30	-	-
GV2P22	20-25	50	50	-	18	-	-	-
GV2ME32	24-32	25	10	50	10	30	-	-
GV2P32	24-32	42	42	-	18	-	-	-
GV3P13	9 – 13	-	-	-	-	-	100	25
GV3P18	12 – 18	-	-	-	-	-	100	25
GV3P25	17 – 25	-	-	-	-	-	100	25
GV3P32	23 – 32	-	-	-	-	-	100	25
GV3P40	30 – 40	-	-	-	-	-	65	25
GV3P50	37 – 50	-	-	-	-	-	65	25
GV3P65	48 – 65	-	-	-	-	-	65	25
GV3P73	62 - 68	-	-	-	-	-	65	25