

Déclaration de conformité Declaration of Conformity

Pour le compte/*Customer's name* : CUMMINS BRASIL
LIMITADA
SDMO ENERGIA IND E
COM DE MAQUINAS

Affaire / *Order* :
Référence / *Reference* : PP_ACB_050_01

Produit :

Product : EasyPact MVS

We undersigned, Schneider Electric, certify EasyPact MVS range of ACBs are suitable for front connection termination from 800 – 3200A with below breaking capacity levels , according to the standard IEC60947-1 and IEC60947-2 :



EasyPact MVS circuit breakers as per IEC 60947-2	MVS08N	MVS10N	MVS16N	MVS20N	MVS25N	MVS32N
Ultimate breaking capacity (kA rms), Icu 220...440V AC 50/60 Hz	42	42	42	50	50	50
Rated service breaking capacity (kA rms), Ics @ 220...440 V AC 50/60 Hz	Ics=100%Icu					
Rated short-time withstand current (kA rms) Icw -> 1s @ 220...440 V AC 50/60 Hz	42	42	42	50	50	50
Rated making capacity (kA peak)Icm 220...440V AC 50/60 Hz	88	88	88	105	105	105
EasyPact MVS circuit breakers as per IEC 60947-2	MVS08H	MVS10H	MVS16H	MVS20H	MVS25H	MVS32H
Ultimate breaking capacity (kA rms), Icu 220...440V AC 50/60 Hz	50	50	50	50	65	65
Rated service breaking capacity (kA rms), Ics @ 220...440 V AC 50/60 Hz	Ics=100%Icu					
Rated short-time withstand current (kA rms) Icw -> 1s @ 220...440 V AC 50/60 Hz	50	50	50	50	65	65
Rated making capacity (kA peak)Icm 220...440V AC 50/60 Hz	105	105	105	105	143	143



Roselyne RUFFEL-LASSAGNE
Schneider Electric Industries SAS (France)
Partner Project Business
Power Breakers Customer Satisfaction & Quality VP