

Definite Purpose Contactor Coil Information

9998DA1

Voltage Code	Voltage Rating	Resistance
V02	120Vac	199.3 Ohms (20°C)
V04	277Vac	1077 Ohms (20°C)
V06	480Vac	3220 Ohms (20°C)
V07	600Vac	4845 Ohms (20°C)
V09	208-240Vac	735 Ohms (20°C)
V14	24Vac	7.94 Ohms (20°C)

For use with:

8910 DPA12 8911DPSO12 8911DPSG12
8910 DPA13 8911DPSO13 8911DPSG13
8910 DPA22 8911DPSO22 8911DPSG22
8910 DPA23 8911DPSO23 8911DPSG23
8910 DPA32 8911DPSO32 8911DPSG32
8910 DPA33 8911DPSO33 8911DPSG33
8910 DPA42 8911DPSO42 8911DPSG42
8910 DPA43 8911DPSO43 8911DPSG43

9998DA2

Voltage Code	Voltage Rating	Resistance
V02	120Vac	90.1 Ohms (20°C)
V04	277Vac	483 Ohms (20°C)
V06	480Vac	1453 Ohms (20°C)
V07	600Vac	2131 Ohms (20°C)
V09	208-240Vac	302 Ohms (20°C)
V14	24Vac	3.62 Ohms (20°C)

For use with:

8910 DPA52 8911DPSO52 8911DPSG52
8910 DPA53 8911DPSO53 8911DPSG53
8910 DPA62
8910 DPA63

9998DA3

Voltage Code	Voltage Rating	Resistance
V02	120Vac	16.1 Ohms (20°C)
V04	277Vac	96.6 Ohms (20°C)
V06	480Vac	267.5 Ohms (20°C)
V07	600Vac	425 Ohms (20°C)
V09	208-240Vac	52.2 Ohms (20°C)
V14	24Vac	0.654 Ohms (20°C)

For use with:

8910 DPA72 8911DPSO63 8911DPSG63

8910 DPA73 8911DPSO73 8911DPSG73

8910 DPA92 8911DPSO93 8911DPSG93

8910 DPA93