

Altistart 22 soft start/soft stop units

Options: fans and accessories

Replacement parts



ATS22D17Q + VW3G2240●



LA9F70●



VZ3V22D1220V



VZ3V22E1110V

Fans

Presentation

ATS22C21Q...C59Q, ATS22C21S6...C59S6, and ATS22C21S6U...C59S6U soft start/soft stop units have an integrated fan.

ATS22D17Q...C17Q, ATS22D17S6...C17QS6, and ATS22D17S6U...C17S6U soft start/soft stop units are ventilated by means of natural convection.

To meet the needs of more demanding applications, such as those with a greater number of starts, the Altistart 22 range offers fans as an option. These are driven by the soft start/soft stop unit and are mounted on the back of the device.

The fan noise level is less than 60 dBA.

References

Description	Control supply voltage V	For soft start/ soft stop unit	Dimensions W x D x H mm/ in.	Reference	Weight kg/ lb
Fans	220	ATS22D17Q...D47Q, ATS22D17S6...D47S6	130 x 40 x 265/ 5.11 x 1.57 x 10.43	VW3G22400	1.200/ 2.646
		ATS22D62Q...D88Q, ATS22D62S6...D88S6	145 x 40 x 295/ 5.71 x 1.57 x 11.61	VW3G22401	1.400/ 3.086
		ATS22C11Q...C17Q, ATS22C11S6...C17S6	150 x 40 x 350/ 5.91 x 1.57 x 13.78	VW3G22402	1.600/ 3.527
	110	ATS22D17S6U...D47S6U	130 x 40 x 265/ 5.11 x 1.57 x 10.43	VW3G22U400	1.200/ 2.646
		ATS22D62S6U...D88S6U	145 x 40 x 295/ 5.71 x 1.57 x 11.61	VW3G22U401	1.400/ 3.086
		ATS22C11S6U...C17S6U	150 x 40 x 350/ 5.91 x 1.57 x 13.78	VW3G22U402	1.600/ 3.527

Protective covers for power terminals (for use with eyelet connectors)

ATSC11Q...C59Q, ATSC11S6...C59S6, and ATSC11S6U...C59S6U soft start/soft stop units have 6 unprotected power terminals. These terminals can be equipped with protective covers.

Description	For soft start/ soft stop unit	Reference	Weight kg/ lb
Set of 6 protective covers	ATS22C11Q...C17Q, ATS22C11S6...C17S6, ATS22C11S6U...C17S6U	LA9F702	0.250/ 0.551
	ATS22C21Q...C59Q, ATS22C21S6...C59S6, ATS22C21S6U...C59S6U	LA9F703 (1)	0.250/ 0.551

Replacement parts

References

Description	Control supply voltage V	For soft start/ soft stop unit	Reference	Weight kg/ lb
Fans	220	ATS22C21Q...C41Q	VZ3V22D1220V	1.145/ 2.524
		ATS22C21S6...C41S6		
		ATS22C48Q...C59Q	VZ3V22E1220V	2.195/ 4.839
		ATS22C48S6...C59S6		
	110	ATS22C21S6U...C41S6U	VZ3V22D1110V	1.145/ 2.524
		ATS22C48S6U...C59S6U	VZ3V22E1110V	2.195/ 4.839

(1) For use with M10 x 35 mm/1.38 in. screws (not supplied).