



LT3 SE00M



LT3 SA00M



LT3 SM00M

Protection units (without fault memory)					
Units with automatic reset with thermistor short-circuit detection					
Connection	Voltage		Output contact	Reference	Weight kg
Cage connectors	~ 50/60 Hz	115 V	N/C	LT3 SE00F	0.220
		230 V	N/C	LT3 SE00M	0.220
	---	24 V	N/C	LT3 SE00BD	0.220

Units with automatic reset with thermistor short-circuit detection					
On front panel: fault and voltage signalling indicator.					
Connection	Voltage		Output contact	Reference	Weight kg
Cage connectors	~ 50/60 Hz	115/230 V	N/C + N/O	LT3 SA00M	0.220
		24/48 V	N/C + N/O	LT3 SA00ED	0.220
	~ 50/60 Hz or ---	24...230 V	2 C/O	LT3 SA00MW	0.220

Protection units (with fault memory)					
Units with manual reset with thermistor short-circuit detection					
On front panel: - fault and voltage signalling indicator, - Test and Reset button.					
Connection	Voltage		Output contact	Reference	Weight kg
Cage connectors	~ 50/60 Hz	400 V	N/C + N/O	LT3 SM00V	0.220
		24/48 V	N/C + N/O	LT3 SM00E	0.220
		115/230 V	N/C + N/O	LT3 SM00M	0.220
	---	24/48 V	N/C + N/O	LT3 SM00ED	0.220
	~ 50/60 Hz or ---	24...230 V	2 C/O	LT3 SM00MW	0.220

(1) PTC: Positive Temperature Coefficient



DA1 TT●●●



DA1 TS●●●

PTC thermistor probes ⁽¹⁾

Description	Nominal Operating Temperature (NOT) ° C	Colour	Sold in lots of	Unit reference	Weight kg
Integrated triple probes	90	Green/green	10	DA1 TT090	0.010
	110	Brown/brown	10	DA1 TT110	0.010
	120	Grey/grey	10	DA1 TT120	0.010
	130	Blue/blue	10	DA1 TT130	0.010
	140	White/blue	10	DA1 TT140	0.010
	150	Black/black	10	DA1 TT150	0.010
	160	Blue/red	10	DA1 TT160	0.010
	170	White/green	10	DA1 TT170	0.010
Surface probes	60	White/grey	10	DA1 TS060	0.005
	70	White/brown	10	DA1 TS070	0.005
	80	White/white	10	DA1 TS080	0.005
	90	Green/green	10	DA1 TS090	0.005
	100	Red/red	10	DA1 TS100	0.005

Accessories (to be ordered separately)

Mounting accessories

Description	Application	Sold in lots of	Unit reference	Weight kg
Adapter	For fixing on C rail DZ5 MB	10	RHZ 66	0.005

Marking accessories

Clip-in markers (maximum of 5 per unit)	Strips of 10 identical numbers (0 to 9)	25	AB1 R● (2)	0.002
	Strips of 10 identical capital letters (A to Z)	25	AB1 G● (2)	0.002

(1) PTC: Positive Temperature Coefficient

(2) When ordering, replace the ● in the reference with the number or letter required.